



## Fabuwood Cabinetry Features and Construction Details

### Allure and Classic

**Framed, Traditional Construction Cabinetry:** 3/4" x 1 1/2" solid wood stiles and rails.

**Warranty:** 5-year limited warranty.

**Backs, Tops and Bottoms:** 1/2" thick Birch veneer plywood with natural finished interiors.

**Shelf construction:** 3/4" thick Birch veneered plywood with matching wood veneer edge banding. All base cabinetry includes an 18" deep adjustable shelf.

**Door Hinges:** Blum 6-way adjustable, open at 110 degrees.

**Drawers:** 5/8" thick solid Birch dovetail drawer box with a 3/8" plywood bottom. Blumotion full extension concealed drawer runners. 3" interior drawer height.

**KCMA:** Certified

### Prima, High-Gloss Acrylic

**Frameless Construction:** 3/4" combi-plywood.

**Warranty:** 5-year limited warranty.

**Backs, Tops and Bottoms:** 3/4" combi-plywood for sides and bottoms. Back panel is 1/4" MDF.

**Shelf construction:** 3/4" combi-plywood adjustable shelving. Base cabinet 18" deep shelves.

**Door Hinges:** Clip-on six-way adjustable self-close hinges.

**Drawers:** Meta-box soft close drawer box with 5/8" combi-plywood bottom. Full extension soft-close slides. 2 7/8" interior drawer height.

**KCMA:** Certified

Note: Wall cabinets are 13" deep with 12" interior depth



### Value and Quest

**Framed, Traditional Construction Cabinetry:** 3/4" x 1 1/2 "solid wood stiles and rails.

**Warranty:** 5-year limited warranty.

**Backs, Tops and Bottoms:** 1/2" thick veneer plywood with natural finished interiors.

**Shelf construction:** 5/8" thick select veneered wood with matching wood edge-banding. Base cabinet has 11 7/8" deep shelf.

**Door Hinges:** 6-way adjustable, concealed hinges open at 110 degrees.

**Drawers:** 5/8" thick solid Birch dovetail drawer box with a 3/8" plywood bottom. Under-mounted epoxy coated slides. 2 1/2" interior drawer height.

**KCMA:** Certified

TROY • SARATOGA SPRINGS • LAKE GEORGE • WESTCHESTER

518.283.1700

[www.ccabinet.com](http://www.ccabinet.com)

914.348.1600